

Suspensiones que serán eliminadas a partir del 01.01.2016	
Código TARIC	DESCRIPTION
2846100040	Cerium lanthanum neodymium praseodymium carbonate, whether or not hydrated
2905299010	3,5-Dimethylhex-1-yn-3-ol (CAS RN 107-54-0)
2921450010	Sodium hydrogen 3-aminonaphthalene-1,5-disulphonate (CAS RN 4681-22-5)
2926909563	1-(Cyanoacetyl)-3-ethylurea (CAS RN 41078-06-2)
2933399947	(-)-trans-4-(4'-Fluorophenyl)-3-hydroxymethyl-N-methylpiperidine (CAS RN 105812-81-5)
2935009030	Mixture of isomers consisting of N-ethyltoluene-2-sulphonamide and N-ethyltoluene-4-sulphonamide
3204190011	Photochromic dye, 3-(4-butoxyphenyl-6,7-dimethoxy-3-(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromene-11-carbonitrile
3204190031	Photochromic dye, N-hexyl -6,7-dimethoxy-3,3-bis(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromene-11-carboxamide
3204190041	Photochromic dye, 4,4'-(13,13-dimethyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromene-3,3-diyl)diphenol
3204190051	Photochromic dye, 4-(4-(6,11-difluoro-13,13-dimethyl-3-phenyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromen-3-yl)phenyl)morpholine (CAS RN 1360882-72-6)
3824909240	Mixture containing two or three of the following acrylates: — urethane acrylates, — tripropylene glycoldiacrylate, — ethoxylated bisphenol A acrylate and — poly(ethyleneglycol) 400 diacrylate
3824909254	Poly(tetramethylene glycol) bis[(9-oxo-9H-thioxanthen-1-yloxy)acetate] with an average polymer chain length of less than 5 monomer units (CAS RN #813452-37-8)
3911909931	Copolymers of butadiene and maleic acid, whether or not containing its ammonium salts
3919108023	Reflecting film, consisting of several layers including: — poly(vinyl chloride); — polyurethane with, on one side, imprints against counterfeiting, alteration or substitution of data or duplication, and on the other side, a layer of glass microspheres; — a layer incorporating a security and/or official mark which changes appearance with angle of view; — metallised aluminium; — and adhesive, covered on one side with a release liner
3919108032	Polytetrafluoroethylene film: — with a thickness of 110 µm or more, — with a surface resistance of between 10 ² -10 ¹⁴ ohms as determined by test method ASTM D 257, — coated on one side with an acrylic pressure sensitive adhesive
3919108037	Polytetrafluoroethylene film: — with a thickness of 100 µm or more, — an elongation at break of not more than 100 %, — coated on one side with a pressure sensitive silicon adhesive
3921905530	Prepreg sheets or rolls containing brominated epoxy resin reinforced with glass fabric, having — a flow of not more than 3,6 mm (as determined by IPC-TM 650.2.3.17.2), and — a glass transition temperature (T _g) of more than 170 °C (as determined by IPC-TM 650.2.4.25) for use in the manufacture of printed circuit boards# (1)

8526912080 8527290010	Integrated audio module (IAM) with a digital video output for connection to an LCD touch screen monitor, interfaced over the Media Oriented Systems Transport (MOST) network and transported over the MOST High protocol, with or without — a printed circuit board (PCB) containing a Global Positioning System (GPS) receiver, a gyroscope, and a Traffic Message Channel (TMC) tuner, — a hard disk drive supporting multiple maps, — a HD radio, — a voice recognition system, — a CD and DVD drive, and including — Bluetooth, MP3 and USB input connectivity, — a voltage of 10 V or more but not more than 16 V, for the use in the manufacture of vehicles in Chapter 87 (1)
--------------------------	--