

Suspensiones en principio con prórroga automática a partir del 01.01.2016	
Código TARIC	PRODUCTO
2008994894	Mango puree: — not from concentrate, — of the genus Mangifera, — of a Brix value of 14 or more, but not more than 20 used in the manufacture of products of drink industry# (1)
2009419220, 2009419970	Pineapple juice: — not from concentrate, — of the genus Ananas, — of a Brix value of 11 or more but not more than 16, used in the manufacture of products of drink industry# (1)
2805309045, 2805309055, 2805309065	Rare-earth metals, scandium and yttrium, of a purity by weight of 95 % or more
2818109110	Sintered corundum with micro crystalline structure, containing by weight: — 94 % or more, but not more than 98,5 % of $\alpha$ -Al <sub>2</sub> O <sub>3</sub> (CAS RN 1344-28-1), — 2 % ( $\pm$ 1,5 %) of magnesium spinel (CAS RN 1309-48-4), — 1 % ( $\pm$ 0,6 %) of yttrium oxide (CAS RN 1314-36-9), and — either 2 % ( $\pm$ 1,2 %) of lanthanum oxide (CAS RN 1312-81-8) — or 2 % ( $\pm$ 1,2 %) of lanthanum oxide (CAS RN 1312-81-8) and neodymium oxide (CAS RN 1313-97-9) with less than 50 % of the total weight having a particle size of more than 10 mm
2826199010	Tungsten hexafluoride with a purity of 99,9 % by weight or more (CAS RN 7783-82-6)
2833298030	Zirconium sulphate (CAS RN 14644-61-2)
2904200010	Nitromethane (CAS RN 75-52-5)
2904200020	Nitroethane (CAS RN 79-24-3)
2904200030	1-Nitropropane (CAS RN 108-03-2)
2905399510	Propane-1,3-diol (CAS RN 504-63-2)
2909309030	3,4,5-Trimethoxytoluene (CAS RN 6443-69-2)
2909500020	Ubiquinol (CAS RN 992-78-9)
2912490030	Salicylaldehyde (CAS RN 90-02-8)
2914290030	(R)-p-Mentha-1(6),8-dien-2-one (CAS RN 6485-40-1)
2914500020	3'-Hydroxyacetophenone (CAS RN 121-71-1)
2914700060	4'-tert-Butyl-2',6'-dimethyl-3',5'-dinitroacetophenone (CAS RN 81-14-1)
2915390060	Dodec-8-enyl acetate (CAS RN 28079-04-1)
2915390065	Dodeca-7,9-dienyl acetate (CAS RN 54364-62-4)
2915390070	Dodec-9-enyl acetate (CAS RN 16974-11-1)
2915907060	Ethyl-6,8-dichlorooctanoate (CAS RN 1070-64-0)
2916130010	Hydroxyzinc methacrylate powder (CAS RN 63451-47-8)
2916200060	3-Cyclohexylpropionic acid (CAS RN 701-97-3)
2916399030	2,4,6-Trimethylbenzoyl chloride (CAS RN 938-18-1)
2917199050	Tetradecanedioic acid (CAS RN 821-38-5)
2917399520	Dibutyl-1,4-benzenedicarboxylate (CAS RN 1962-75-0)
2917399530	Benzene-1,2:4,5-tetracarboxylic dianhydride (CAS RN 89-32-7)
2920908520	Tris(methylphenyl)phosphite (CAS RN 25586-42-9)
2920908530	2,2'-[[[3,3',5,5'-Tetrakis(1,1-dimethylethyl)[1,1'-biphenyl]-2,2'-diyl]bis(oxy)]bis[biphenyl-1,3,2-dioxaphosphine], (CAS RN 138776-88-2)
2920908540	Bis(2,4-dicumylphenyl)pentaerythritol diphosphite (CAS RN 154862-43-8)

2921290040	Decamethylenediamine (CAS RN 646-25-3)
2921309930	1,3-Cyclohexanedimethanamine (CAS RN 2579-20-6)
2921430050	4-Aminobenzotrifluoride (CAS RN 455-14-1)
2921430060	3-Aminobenzotrifluoride (CAS RN 98-16-8)
2921490080	4-Heptafluoroisopropyl-2-methylaniline (CAS RN 238098-26-5)
2922290075	4-(2-Aminoethyl)phenol (CAS RN 51-67-2)
2922390020	2-Amino-5-chlorobenzophenone (CAS RN 719-59-5)
2922498545	Glycine (CAS RN 56-40-6)
2923900075	Tetraethylammonium hydroxide, in the form of an aqueous solution containing: — 35 % (± 0,5 %) by weight of tetraethylammonium hydroxide, — not more than 1 000 mg/kg of chloride, — not more than 2 mg/kg of iron and — not more than 10 mg/kg of potassium
2924299840	N,N'-1,4-Phenylenebis[3-oxobutyramide], (CAS RN 24731-73-5)
2924299845	Propoxur (ISO) (CAS RN 114-26-1)
2924299855	N,N'-(2,5-Dimethyl-1,4-phenylene)bis[3-oxobutyramide], (CAS RN 24304-50-5)
2924299860	N,N'-(2-Chloro-5-methyl-1,4-phenylene)bis[3-oxobutyramide], (CAS RN 41131-65-1)
2928009025	Acetaldehyde oxime in an aqueous solution (CAS RN 107-29-9)
2930909910	2,3-Bis((2-mercaptoethyl)thio)-1-propanethiol (CAS RN 131538-00-6)
2930909955	Thiourea (CAS RN 62-56-6)
2931908005	Diethylmethoxyborane (CAS RN 7397-46-8), whether or not in the form of a solution in tetrahydrofuran according to note 1e to Chapter 29 of the CN
2932990050	7-Methyl-3,4-dihydro-2H-1,5-benzodioxepin-3-one (CAS RN 28940-11-6)
2933210080	5,5-Dimethylhydantoin (CAS RN 77-71-4)
2933399920	Copper pyrrhione powder (CAS RN 14915-37-8)
2933399985	2-Chloro-5-chloromethylpyridine (CAS RN 70258-18-3)
2933499030	Quinoline (CAS RN 91-22-5)
2933499040	Isoquinoline (CAS RN 119-65-3)
2933698055	Terbutryn (ISO) (CAS RN 886-50-0)
2933698060	Cyanuric acid (CAS RN 108-80-5)
2933790070	(S)-N-[(Diethylamino)methyl]-alpha-ethyl-2-oxo-1-pyrrolidineacetamide L-(+)-tartrate, (CAS RN 754186-36-2)
2934208060	Benzothiazol-2-yl-(Z)-2-trityloxyimino-2-(2-aminothiazole-4-yl)-thioacetate (CAS RN 143183-03-3)
2934208070	N,N-Bis(1,3-benzothiazol-2-ylsulphanyl)-2-methylpropan-2-amine (CAS RN 3741-80-8)
2934999025	2,4-Diethyl-9H-thioxanthen-9-one (CAS RN 82799-44-8)
2934999050	10-[1,1'-Biphenyl]-4-yl-2-(1-methylethyl)-9-oxo-9H-thioxanthenium hexafluorophosphate, (CAS RN 591773-92-1)
2934999086	Dithianon (ISO) (CAS RN 3347-22-6)
2934999087	2,2'-(1,4-Phenylene)bis(4H-3,1-benzoxazin-4-one) (CAS RN 18600-59-4)
2935009042	Penoxsulam (ISO) (CAS RN 219714-96-2)
2938903010	Ammonium glycyrrhizate (CAS RN 53956-04-0)

3204110020	Colourant C.I. Disperse Yellow 241 (CAS RN 83249-52-9) and preparations based thereon with a colourant C.I. Disperse Yellow 241 content of 97 % or more by weight
3204110030	Preparation of dispersion dyes, containing: — C.I. Disperse Orange 61, — C.I. Disperse Blue 291:1, — C.I. Disperse Violet 93:1, — C.I. Disperse Red 54
3204190071	Colourant C.I. Solvent Brown 53 (CAS RN 64696-98-6) and preparations based thereon with a colourant C.I. Solvent Brown 53 content of 95 % or more by weight
3204190073	Colourant C.I. Solvent Blue 104 (CAS RN 116-75-6) and preparations based thereon with a colourant C.I. Solvent Blue 104 content of 97 % or more by weight
3215900040	Dry ink powder with a base of hybrid resin (made from polystyrene acrylic resin and polyester resin) mixed with: — wax; — a vinyl-based polymer and — a colouring agent for use in the manufacture of toner bottles for photocopiers, fax machines, printers and multifunction devices# (1)
3402119010	Sodium lauroyl methyl isethionate
3402901030	Surface-active preparation, consisting of a mixture of sodium docusate and ethoxylated 2,4,7,9-tetramethyldec-5-yne-4,7-diol (CAS RN 577-11-7 and 9014-85-1)
3402901050	Surface-active preparation, consisting of a mixture of polysiloxane and poly(ethylene glycol)
3402901060	Surface-active preparation, containing 2-ethylhexyloxymethyl oxirane
3707909080	Anti-reflection coating, consisting of either a siloxane polymer or an organic polymer having a phenolic hydroxy group modified with a chromophore group, in the form of a solution of an organic solvent containing either 1-ethoxy-2-propanol or 2-methoxy-1-methylethyl acetate containing by weight not more than 10 % of polymer
3808939020	Preparation consisting of benzyl(purin-6-yl)amine in a glycol solution, containing by weight: — 1,88 % or more but not more than 2,00 % of benzyl(purin-6-yl)amine of a kind used in plant growth regulators
3808939030	Aqueous solution containing by weight: — 1,8 % of sodium para-nitrophenolate, — 1,2 % of sodium ortho-nitrophenolate, — 0,6 % of sodium 5-nitroguaiacolate for use in the manufacture of a plant growth regulator # (1)
3808939040	Mixed white powder containing by weight: — 3 % or more but not more than 3,6 % of 1-methylcyclopropene with a purity more than 96 % and — containing less than 0,05 % of each impurity of 1-chloro-2-methylpropene and 3-chloro-2-methylpropene for use in the manufacture of a growth regulator of post-harvest fruits, vegetables and ornamentals with a specific generator# (1)

3808939050	Preparation in the form of powder, containing by weight: — 55 % or more of Gibberellin A4, — 1 % or more but not more than 35 % of Gibberellin A7, — 90 % or more of Gibberellin A4 and Gibberellin A7 combined — not more than 10 % of a combination of water and other naturally occurring Gibberellins of a kind used in plant growth regulators
3808999010	Oxamyl (ISO) (CAS RN 23135-22-0) in a solution of cyclohexanone and water
3815909030	Catalyst, consisting of a suspension in mineral oil of: — tetrahydrofuran complexes of magnesium chloride and titanium(III) chloride; and — silicon dioxide — containing 6,6 % ( $\pm$ 0,6 %) by weight of magnesium, and — containing 2,3 % ( $\pm$ 0,2 %) by weight of titanium
3815909080	Catalyst consisting predominantly of dinonylnaphthalenedisulphonic acid in the form of a solution in isobutanol
3824909244	Preparation containing by weight: — 85 % or more but not more than 95 % of $\alpha$ -4-(2-cyano-2-butoxycarbonyl)vinyl-2-methoxyphenyl- $\omega$ -hydroxyhexa(oxyethylene), and — 5 % or more but not more than 15 % of polyoxyethylene (20) sorbitan monopalmitate
3824909246	Diethylmethoxyborane (CAS RN 7397-46-8) in the form of a solution in tetrahydrofuran
3824909260	N2-[1-(S)-Ethoxycarbonyl-3-phenylpropyl]-N6-trifluoroacetyl-L-lysyl-N2-carboxy anhydride in a solution of dichloromethane at 37 %
3824909261	3',4',5'-Trifluorobiphenyl-2-amine, in the form of a solution in toluene containing by weight 80 % or more but not more than 90 % of 3',4',5'-trifluorobiphenyl-2-amine
3901300080	Ethylene-vinyl acetate copolymer, — containing 27,8 % or more but not more than 29,3 % by weight of vinyl acetate — with a melt flow index of 22 g/10 min or more but no more than 28 g/10 min — containing not more than 15 mg/kg vinyl acetate monomer
3901909080	Block copolymer of ethylene with octene in the form of pellets: — with a specific gravity of 0,862 or more, but not more than 0,865, — able to stretch to at least 200 % its original length, — with a hysteresis of 50 % ( $\pm$ 10 %), — with permanent deformation of not more than 20 %, for use in the manufacture of napkin liners for babies # (1)
3901909082	Copolymer of ethylene and methacrylic acid
3902100050	High isotactic polypropylene (HIPP), whether or not coloured, intended for the manufacture of plastic components for air freshener with the following properties: — a density of 0,880 g/cm <sup>3</sup> or more but not more than 0,913 g/cm <sup>3</sup> (as determined by test method ASTM D1505), — a tensile strength at yield of 350 kg/cm <sup>2</sup> or more but not more than 390 kg/cm <sup>2</sup> (as determined by test method ASTM D638) — a heat deflection temperature of 135 °C or more under load of 0,45 MPa (as determined by test method ASTM 648) (1)

3904698081	Poly(vinylidene fluoride) (CAS RN 24937-79-9)
3906909040	Transparent acrylic polymer in packages of not more than 1 kg, and not for retail sale with: — a viscosity of not more than 50000 Pa•s at 120 °C as determined by the test method ASTM D 3835 — a weight average molecular weight (Mw) of more than 500 000 but not more than 1 200 000 according to the Gel Permeation Chromatography (GPC) test, — a residual monomer content of less than 1 %
3907999030, 3913900020	Poly(hydroxyalkanoate), predominantly consisting of poly(3-hydroxybutyrate)#
3907999080	Copolymer, consisting of 72 % by weight or more of terephthalic acid and/ or derivatives thereof and cyclohexanedimethanol, completed with linear and/ or cyclic dioles
3909400020	Powder of thermosetting resin in which magnetic particles have been evenly distributed, for use in the manufacture of ink for photocopiers, fax machines, printers and multifunction devices# (1)
3911909930	1,4:5,8- Dimethanonaphthalene, 2-ethylidene-1,2,3,4,4a,5,8,8a-octahydro-, polymer with 3a,4,7,7a- tetrahydro- 4,7-methano-1H-indene, hydrogenated
3911909935	Alternated copolymer of ethylene and maleic anhydride (EMA)
3912110040	Cellulose diacetate powder
3919108043, 3919900026	Ethylene vinyl acetate film: — of a thickness of 100 µm or more, — coated on one side with an acrylic pressure sensitive or UV-sensitive adhesive and a polyester or polypropylene liner.
3919900060	Reflecting film containing: — a poly(vinyl chloride) layer, — a polyurethane layer, — a glass microspheres layer, — a layer whether or not incorporating a security and/or official mark which changes appearance with angle of view, — a metallised aluminium layer, and — an adhesive, covered on one side with a release liner
3919900063	Co-extruded trilayer film, — each layer containing a mixture of polypropylene and polyethylene, — containing not more than 3 % by weight of other polymers, — whether or not containing titanium dioxide in the core layer, — coated with an acrylic pressure sensitive adhesive and — with a release liner — of an overall thickness of not more than 110 µm
3919900065	Self-adhesive film with a thickness of 40 µm or more, but not more than 400 µm, consisting of one or more layers of transparent, metallised or dyed poly(ethylene terephthalate), covered on one side with a scratch resistant coating and on the other side with a pressure sensitive adhesive and a release liner
3919900070	Self-adhesive polishing discs of microporous polyurethane, whether or not coated with a pad
3920621948	Sheets or rolls of poly(ethylene terephthalate): — coated on both sides with a layer of epoxy acrylic resin, — of a total thickness of 37 µm (± 3 µm)

5402470020	Bicomponent monofilament yarn of not more than 30 dtex, consisting of: — a poly(ethylene terephthalate) core, and — an outer layer of a copolymer of poly(ethyleneterephthalate) and poly(ethyleneisophthalate), for use in the manufacture of filtration fabrics# (1)
5603131020	Non-woven of spunbonded polyethylene, with a coating, — of a weight of more than 80 g/m <sup>2</sup> but not more than 105 g/m <sup>2</sup> and — an air resistance (Gurley) of 8 seconds or more but not more than 75 seconds (as determined by the ISO 5636/5 method)
6909190020	Silicon nitride (Si <sub>3</sub> N <sub>4</sub> ) rollers or balls
7009910010	Unframed glass mirrors with: — a length of 1516 mm (± 1 mm); — a width of 553 mm (± 1 mm); — a thickness of 3 mm (± 0,1 mm); — the back of the mirror covered with protective polyethylene (PE) film, with a thickness of 0,11 mm or more but not more than 0,13 mm; — a lead content of not more than 90 mg/kg and — a corrosion resistance of 72 hours or more according to ISO 9227 salt spray test
7019191020	Yarn of 10,3 tex or more but not more than 11,9 tex, obtained from continuous spun-glass filaments, in which filaments of a diameter of 4,83 µm or more but not more than 5,83 µm predominate
7019191025	Yarn of 5,1 tex or more but not more than 6,0 tex, obtained from continuous spun-glass filaments, in which filaments of a diameter of 4,83 µm or more but not more than 5,83 µm predominate
7202998010	Ferro-dysprosium, containing by weight: — 78 % or more of dysprosium, and — 18 % or more but not more than 22 % of iron
7604291010, 7606129920	Sheets and bars of aluminium-lithium alloys#
8104300030	Magnesium powder: — of purity by weight of 99,5 % or more, — with a particle size of 0,2 mm or more but not more than 0,8 mm
8108903030	Titanium-aluminium-vanadium alloy (TiAl6V4) wire, complying with AMS standards 4928 and 4967

8301600010, 8413910020, 8419908520, 8438900010, 8468900010, 8476900010, 8479908087, 8481900020, 8503009945, 8515900020, 8531908520, 8536908596, 8543900050, 8708919910, 8708999730, 9031908530	Keypads, wholly of either silicone or polycarbonate, including printed keys with electrical contacting elements.
8407909020	Compact Liquid Petroleum Gas (LPG) Engine System, with: — 6 cylinders, — an output of 75 kW or more, but not more than 80 kW, — inlet and exhaust valves modified to operate continuously in heavy duty applications, for use in the manufacture of vehicles of heading 8427# (1)
8413703520	Single phase centrifugal pump: — discharging at least 400 cm <sup>3</sup> fluid per minute, — with a noise level limited to 6 dBA, — with the inside diameter of the suction opening and discharge outlet of not more than 15 mm, and — working at ambient temperatures down to -10°C
8414592040	Axial fan with an electric motor, of an output of not more than 2 W, for use in the manufacture of products of heading 8521 or 8528 # (1)
8479899750, 8479908080	Machinery, being components of a production line for the manufacture of lithium ion batteries for passenger electric motor vehicles, for the construction of such a production line# (1)#
8483409080	Transmission gearbox, with: — not more than 3 gears, — an automatic deceleration system and — a power reversal system, for use in the manufacture of goods of heading 8427 # (1)
8504509540	Coil choke with: — an inductance of 4,7 µH (± 20 %), — a DC resistance of not more than 0,1 Ohms, — an insulation resistance of 100 MOhms or more at 500 V (DC) for use in the manufacture of LCD and LED module power boards # (1)
8507102080	Lead acid starter battery, with: — a charge acceptance capacity of 200 % or more of the level of an equivalent conventional flooded battery during the first 5 seconds of charge, — a liquid electrolyte, for use in the manufacture of passenger cars and light commercial vehicles employing high regenerative alternator controls or start/stop systems with high regenerative alternator controls # (1)

8507600060	Lithium-ion rechargeable batteries, with: — a length of 1 213 mm or more, but not more than 1 575 mm, — a width of 245 mm or more but not more than 1 200 mm, — a height of 265 mm or more, but not more than 755 mm, — a weight of 265 kg or more but not more than 294 kg, — a nominal capacity of 66,6 Ah, put up in packs of 48 modules
8507600070	Rectangular modules for incorporation in lithium-ion rechargeable batteries: — of a length of 350 mm or 312 mm, — of a width of 79,8 mm or 225 mm, — of a height of 168 mm or 35 mm, — of a weight of 6,2 kg or 3,95 kg, — with a rating of 129 Ah or 66,6 Ah
8507600080	Rectangular lithium-ion-accumulator or module, with — a metal casing, — a length of 171 mm ( $\pm 3$ mm), — a width of 45,5 mm ( $\pm 1$ mm), — a height of 115 mm ( $\pm 1$ mm), — a nominal voltage of 3,75 V and — a nominal capacity of 50 Ah for use in the manufacture of rechargeable batteries for motor vehicles# (1)
8508700010, 8537109996	Electronic circuit card without separate housing for actuating and controlling vacuum cleaner brushes powered by not more than 300 W#
8508700020, 8537109998	Electronic circuit cards that: — are connected by wire or radio frequency to each other and the motor controller card, and — regulate the functioning (switching on or off and suction capacity) of vacuum cleaners according to a stored program, — whether or not fitted with indicators that display the functioning of the vacuum cleaner (suction capacity and/or dust bag full and/or filter full) #
8518408092	Circuit board sub-assembly, comprising power supply, active equalizer and power amplifier circuits
8529906565	Printed circuit board for distributing supply voltage and control signals directly to a control circuit on a TFT glass panel of a LCD module
8529909225	LCD modules, not combined with touch screen facilities, solely consisting of: — one or more TFT glass or plastic cells, — a die cast heat sink, — a backlight unit, — one printed circuit board with micro controller, and — LVDS (Low Voltage Differential Signalling) interface, for use in the manufacture of radios for motor vehicles # (1)
8529909250	Colour LCD display panel for LCD monitors of heading 8528: — with a diagonal measurement of the screen of 14,48 cm or more but not more than 31,24 cm, — with backlight, micro-controller, — with a CAN (Controller area network)-controller with LVDS (Low-voltage differential signalling) interface and CAN/power supply socket or with an APIX (Automotive Pixel Link) controller with APIX interface, — in a housing with or without a heat sink at the back of the housing, — without a signal-processing module, for use in the manufacture of vehicles of chapter 87# (1)



8535900030, 8536508083	Semiconductor module switch in a casing: — consisting of an IGBT transistor chip and a diode chip on one or more lead frames, — for a voltage of 600 V or 1 200 V #
8536699084	Universal serial bus (USB) socket or plug in a single or multiple form for connecting with other USB devices, for use in the manufacture of goods falling within headings 8521 or 8528# (1)
8543709040	High-frequency amplifier comprising one or more integrated circuits and discrete capacitor chips on a metal flange in a housing
8543709095	Mobile telephone view and control module comprising of: — a mains power/ CAN (Controller area network) output socket, — a universal serial bus (USB) and audio IN/OUT ports and — incorporating a video switching device for the interface of smart phone operating systems with the Media Orientated Systems Transport network (MOST), for use in the manufacture of vehicles of Chapter 87 # (1)
8545909020	Carbon fibre paper of a kind used for gas diffusion layers in fuel cell electrodes
8708309110	Drum type parking brake: — operating within the service brake disk, — with a diameter of 170 mm or more but not more than 175 mm, for use in the manufacture of motor vehicles# (1)
9001900085	Light guide panel made of poly(methyl methacrylate): — whether or not cut, — whether or not printed, for use in the manufacture of backlight units for flat screen TVs# (1)
9401908010	Ratchet disk of a kind used in the manufacture of reclining car seats
9503007510, 9503009510	Plastic cable car scale models, whether or not with a motor, for printing (1)